

Did You Know...?



WOLFINGTON
body company, inc.

Need Service?

In Eastern PA & DE, call
800-662-2435

James Titus—Dir of Parts & Serv
Ext. 6421

Dane Colestock—VP, Parts Sales
Ext. 6603

Terry Breyer—Assist Parts Mgr
Ext. 6604

David Ruth—Service Manager
Ext 6461

Tony Davis—Service Writer
Ext. 6464

Jim Caudill—Body Shop Super.
Ext. 6463

In Central PA, call
800-248-9197

Bill Quigley—Service

In New Jersey, call
800-328-7636

Frank Reed—Parts & Serv Mgr
Ext. 7122

Sherri West—Assist. Parts Mgr
Ext. 7120

New Low Ash CJ-4 Oils

Did you know that all engines manufactured after January 1, 2007 (also known as post-emissions) require the new low ash, CJ-4 engine oils? CJ-4 replaces the use of the previous oil, CI-4, and is necessary to maintain the International engine warranty. CJ-4, in combination with Ultra Low Sulfur Diesel (ULSD), is essential to maintain performance and durability of the new aftertreatment systems. CJ-4 has specifically designed additive systems that are necessary for the proper protection of the power train and aftertreatment systems. The oil drain interval should not be affected by the use of CJ-4, in combination with ULSD, from your previous engines. CJ-4 was made to work in conjunction with ULSD since the fuel requires oil with higher lubrication. CJ-4 can have a positive benefit when used in engines made after 1993. The new oil will reduce sludge deposits in all diesel engines. CJ-4 has also been designed to be more fluid at lower temperatures, allowing for easier cold morning starts. For any questions or helpful information, refer to your owner's manual or contact one of our helpful service technicians.



MAXXFORCE 7
INTERNATIONAL DIESEL POWER™



MAXXFORCE DT
INTERNATIONAL DIESEL POWER™

The Importance of New Extended Life Coolant

Rotella Extended Life Coolant (RELC) is now the standard for all International vehicles. RELC has a service life of 150,000 miles, 2-1/2 years, or 6,000 hours*. RELC provides protection down to -40 degrees F. Only use RELC when topping off the cooling system as a failure to do so will result in reduction of the extended life properties. RELC is available in a 50/50 premix solution.

*[Life cycle can be 300,000 miles/5 yrs/12,000 hours if Extender is added at 150K miles. If your vehicle is equipped with the optional coolant filter, it must be changed when Extender is added.]

Visit us on the web at www.wolffington.com

For any past "Did You Know" publications, contact Ryan Hillanbrand, Sales Rep at extension 6411.

